



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

Pressure-Induced (δ) to (α)' Phase Transformations in a Pu-Ga Alloy

A. J. Schwartz, M. A. Wall, D. L. Farber, J. R. Jeffries, K. J. M. Blobaum

June 10, 2009

IXth US-Russian Workshop on the Fundamentals of Pu Science
Pleasanton, CA, United States
July 18, 2009 through July 19, 2009

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

Pressure-Induced δ to α' Phase Transformations in a Pu-Ga Alloy

A.J. Schwartz, M.A. Wall, D.L. Farber, J.R. Jeffries, and K.J.M. Blobaum
Lawrence Livermore National Laboratory, Livermore, CA 94550, USA

Well-homogenized Pu-2 at.% Ga alloys can be retained in the metastable face centered cubic δ phase at room temperature. Ultimately, this metastable δ phase will decompose via a eutectoid transformation to the thermodynamically stable monoclinic α phase and the intermetallic compound Pu_3Ga over a period of approximately 10,000 years. In addition, these low solute-containing δ -phase Pu alloys are also metastable with respect to low temperature excursions or increases in pressure. δ -phase alloys are known to undergo an incomplete isothermal martensitic phase transformation that results in a microstructure consisting of $\sim 20\text{ }\mu\text{m}$ long lath-shaped particles of the α' phase dispersed within the δ matrix. The $\sim 20\%$ volume contraction between the δ and α' phases requires significant elastic and plastic accommodation. Transmission electron microscopy (TEM) has shown that the dislocation density in the vicinity of the tips of the α' particles is about an order of magnitude larger than in the δ -phase matrix. The δ -phase will also transform to the monoclinic α' phase at slightly elevated pressure. In this study, δ -phase Pu-Ga specimens, 2.3 mm diameter by 100 microns thick were compressed to approximately 1 GPa in a large volume moissanite anvil cell – shown in Figure 1 – to induce the transformation to α' .




Fig. 1. Photograph of large volume moissanite anvil cell used for compressing TEM-sized samples.

The recovered samples were characterized at ambient pressure with optical microscopy, x-ray diffraction, and transmission electron microscopy. Optical microscopy revealed a very fine microstructure that appears to be single phase. This preliminary conclusion was supported by x-ray diffraction, which showed only the monoclinic reflections from the α' phase. However, TEM and electron diffraction revealed small regions of δ phase with a very high dislocation density interspersed between the 10 – 100 nm α' grains as shown in Figure 2.




Fig. 2. Bright-field TEM image of a Pu – 2.0 at.% Ga sample that was compressed to 1 GPa and characterized at ambient pressure. The insert shows an electron diffraction pattern from a neighboring area that reveals Bragg peaks from both the α' and δ phases.

This work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.